

Caesarstone Porcelain Safety Data Sheet



March 2022

1. Product and Company Identification

Product Name: Caesarstone® Porcelain

SDS Preparation Date: March 2022

Product Use: Designed for use in interior and exterior construction, including kitchen countertops, sinks, wall cladding panels, backsplashes and other similar uses.

Avoided Uses: Do not Fabricate the product by using dry processes which generate dust such as sawing, grinding, routing, drilling and sanding, etc.

Company	Address	Emergency Phone
Caesarstone Ltd.	MP Menashe, 3780400, Israel www.caesarstone.com sdsinfo@caesarstone.com	+972-4-610-9368
Caesarstone USA Inc.	1401 W. Morehead, Charlotte, NC 28208, USA	+1-818-779-0999
Caesarstone Canada Inc.	350 Caldari Rd., Concord, Ontario L4K 4J4, Canada	+1-416-322-4000
Caesarstone Australia Pty Ltd.	Moorebank Business Park, Warehouse 3a East, 400 Moorebank Ave, Moorebank, NSW 2170, Australia	+61-13 11 26 / +13
Caesarstone South East Asia Pte Ltd.	10 Bukit Batok Crescent, #08-06, The Spire, Singapore 658079	+65-6316-1938
Caesarstone (UK) Ltd.	Unit 3, Navigation Park, Enfield EN3 4NQ, United Kingdom	+44-800-1588088

2. Hazards Identification

The finished Caesarstone® Porcelain product poses no immediate hazard to health Regulation (EC) No 1272/2008. However, dust derived from cutting, grinding, chipping, sanding, drilling, polishing, etc. during Fabrication Processes contains respirable crystalline silica (SiO₂). Hence, workers involved in Fabricating, installing and demolishing/removing Caesarstone® Porcelain countertops, without correct safety measures in place, are at risk for significant crystalline silica exposure, which can cause serious illnesses including silicosis, lung cancer, chronic obstructive pulmonary disease (COPD), and, rarely, kidney disease and auto-immune disease. During the Fabrication and installation of the product, it is necessary to consider the following information.

* “Fabrication Process/es” or “Fabricating” or “Fabrication” means cutting, grinding, chipping, sanding, drilling, polishing, etc. manufacturing processes, including during installation or removal of the product.

In this SDS Caesarstone® Porcelain slabs are referred to also as “products”.

LABEL ELEMENTS - PLEASE READ CAREFULLY:

REGULATION (EC) No 1272/2008 (CLP) GHS ver.7:

The following relates to the formation of dust, e.g., during Fabrication Processes.

DANGER!



Category 1A (H350)
Category 1 (H372)



Category 3 (H335)

HAZARD STATEMENTS:¹

- (H350) May cause CANCER (inhalation) - Category 1A
Specific target organ toxicity following repeated exposure (STOT RE)
- (H372) Causes damage to lungs through prolonged or repeated exposure (inhalation) - Category 1
Specific target organ toxicity - single exposure (STOS-SE)
- (H335) May cause respiratory tract irritation - Category 3

PREVENTION:¹

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260+P261 Do not breathe dust generated in the Fabrication, installation, and/or removing/demolition process including during cutting, grinding, and polishing.
- P264 Wash face and hands thoroughly after handling and fabricating.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P284 In case of inadequate ventilation, wear respiratory protection for particles (P3/N95 or higher).

¹ Globally Harmonized System of Classification and Labelling of Chemicals (GHS)-UNECE-GHS (Rev.7) (2017).

- P272 Contaminated work clothing should not be allowed out of the workplace.
- P263 Wash contaminated clothing before reuse.

Refer to Section 7 for Handling & Storage details and to Section 8 for dust Exposure Controls.

FIRST AID MEASURES:¹



- P314 Get medical advice/attention if you feel unwell.
- P304+340 If inhaled, remove person to fresh air and keep comfortable for breathing.

DISPOSAL:¹

P501 Dispose of remains in accordance with local regulations.

Refer to Section 13 for Disposal Considerations.



CALIFORNIA PROPOSITION 65 WARNING: This product contains chemicals, including silica, that become airborne and respirable when fabricating the product and are classified by the State of California as causing cancer and birth defects. For information see www.p65warnings.ca.gov.

Potential Health Effects

INHALATION:

Do not breathe dust.

Workers who inhale very small crystalline silica particles are at risk for silicosis - an incurable, progressively disabling and sometimes fatal lung disease. Silicosis results in permanent lung damage. Silica dust particles become trapped in lung tissue, causing inflammation and scarring and reducing the lungs' ability to take in oxygen. Symptoms of silicosis can include shortness of breath, cough and fatigue, and may or may not be obviously attributable to silica. According to the USA OSHA alert of Feb 2015, workers exposed to airborne crystalline silica also are at increased risk for lung cancer, chronic obstructive pulmonary disease (COPD), and, rarely, kidney disease and auto-immune disease (for example rheumatoid arthritis). Risk of disease is dependent on the duration and level of exposure.

SKIN AND EYE CONTACT:

Mineral dust may produce transitory mechanical irritation to the skin and eyes.

AGGRAVATION OF PRE-EXISTING CONDITIONS:

Persons with chronic respiratory disorders or impaired respiratory function may be more susceptible to the effects of this substance and may be adversely affected by any airborne particulate matter exposure. Smoking can increase the risk of lung injury. Inhalation may increase the progression of tuberculosis. Persons with preexisting skin disorders may be more susceptible to the effects of this material.

OTHER HAZARDS

This mixture does not meet bioaccumulative of toxic (PBT) or very persistent or very bioaccumulative (vPvB) standards according to Regulation (EC) No. 1907/2006, Annex XIII.

¹ Globally Harmonized System of Classification and Labelling of Chemicals (GHS)-UNECE-GHS (Rev.7) (2017).

3. Composition/Information on Ingredients

SUBSTANCES:

N/A

MIXTURES:

The product is produced using natural occurring minerals such as feldspar (40-70%), quartz (<20%), and clay (20-40%) mixed with water and different pigments including zircon (depending on product, <12%).

After firing at high temperatures, the product creates a uniform product.

The finished porcelain slab may be improved by adhering a fiberglass mesh to its bottom part using a polyurethane adhesive for improved performance.

The final product does not release hazardous materials or particles after installation.

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No 1272/2008:

Ingredient Name	CAS Number	%	Classification Regulation (EC) no. 1272/2008
Feldspar	68476-25-5	40-70	STOT RE2 (H373)
Clay	1302-62-1	20-40	-
Quartz/Silica sand	14808-60-7	<20	Carc 1A (H350i) STOT RE1 (372i) STOT SE3 (H335i)
Zircon (ZrSiO ₄)	10101-52-7	<12	-

Refer to Section 8 for mixture components subject to occupational exposure limits.

4. First Aid Measures

General advice:

Caesarstone® Porcelain surfaces are not hazardous as shipped. However, Fabrication of the product, including sawing, grinding, routing, drilling and sanding can generate dust, and the following apply:

EYE CONTACT WITH DUST:

Rinse eyes with plenty of room-temperature water for at least 15 minutes. Seek immediate medical attention. Have an emergency eyewash station available in areas where the product is Fabricated.

SKIN CONTACT WITH DUST:

Wash affected area with soap and plenty of water. Seek medical attention if adverse effects occur.

INHALATION OF DUST:

Do not inhale dust generated in the Fabrication, installation, and/or removing/demolition process. Remove person to fresh air. If breathing has stopped, administer artificial respiration. Seek immediate medical attention.

INGESTION OF DUST:

The product in its marketed form is inert. If large amounts are swallowed, seek medical attention.

Most important symptoms, acute and delayed effects:

INHALATION:

Workers who inhale very small crystalline silica particles are at risk for silicosis - an incurable, progressively disabling and sometimes fatal lung disease. Silicosis results in permanent lung damage. Silica dust particles become trapped in lung tissue, causing inflammation and scarring and reducing the lungs' ability to take in oxygen. Symptoms of silicosis can include shortness of breath, cough and fatigue, and may or may not be obviously attributable to silica. According to the USA OSHA alert of Feb 2015, workers exposed to airborne crystalline silica also are at increased risk for lung cancer, chronic obstructive pulmonary disease (COPD), and, rarely, kidney disease and auto-immune disease (for example rheumatoid arthritis). Risk of disease is dependent on the duration and level of exposure.

5. Fire Fighting Measures

- **Extinguishing Media:** Water, dry chemical, CO₂ and foam.
- **Special hazards arising from the substance or mixture:** not flammable. If the product is reinforced on the back side with an embedded fiberglass mesh, the binder and adhesive components start degrading at temperatures over 200°C with formation of gases that may contain various hydrocarbons, carbon dioxide, carbon monoxide, nitrogen oxides and partially un-burnt carbon compounds, depending on the combustion conditions.
- **Advice for Firefighters:** Keep personnel away and upwind of fire. Use self-contained breathing apparatus with full face mask.

6. Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES; ENVIRONMENTAL PRECAUTIONS:

N/A - The finished product does not represent a risk of spillage.

CLEANUP AND DISPOSAL OF SPILL:

Solid slabs can simply be gathered, double bagged, and disposed of as necessary. However, if large amounts of dust or waste is created by cutting during Fabrication Processes, use a high efficiency particulate air (HEPA) vacuum or dampen spilled material with water and sweep up wet material to avoid dust generation - DO NOT DRY SWEEP. Wear suitable respiratory protection and protective clothing. If large quantities of this material enter the waterways, contact the Federal, State, or local Waste Management Authority. Dispose of waste in accordance with local, state and federal regulations.

Refer to Section 8 for personal protective equipment and to Section 13 for waste treatment.

7. Handling and Storage

MANUAL HANDLING:

Wear safety shoes and gloves² during manual handling and storage operations of Caesarstone® Porcelain slabs. The product is heavy and breakable; handle with care to avoid injury and prevent damage. Use certified safe handling systems with appropriate adjustments to the product.

FABRICATING, INSTALLING AND REMOVING:

When Fabricating (cutting, grinding, polishing, drilling, etc. processes) the product, installing or removing/demolishing the installed product, use equipment with integrated water delivery system and integral dust collection and/or use local exhaust ventilation to maintain the ambient workplace atmosphere below the relevant occupational exposure limits.

Do not fabricate the product by using dry processes, which generate hazardous dust. Do not use dry sweeping or compressed air for cleanup, as it causes dust to be airborne. Avoid breathing dust when Fabricating, installing or removing/demolishing product.

Fabricate in a well-ventilated area or use local exhaust venting to maintain the ambient workplace atmosphere below the relevant occupational exposure limits. Use respiratory protective equipment and other personal protective equipment. Restrict access to hazardous dust areas. Wash face and hands thoroughly after fabricating, installing or removing/demolishing the product. Do not eat, drink or smoke when fabricating this product. Leave working clothes at the workplace and wash separately.

Employers should consult with a trained occupational safety and health professional in order to assess the employer's engineering controls and crystalline silica programs, policies and procedures and monitor the air in their workplace and in order to determine worker exposures to hazardous dust and comply with applicable local regulations.

Refer to Section 8 for Exposure Control and Personal Protection details.

It is also recommended to follow Caesarstone Good Practice Guide relating to occupational health and safety in a respirable crystalline silica dust (RCS) environment at: mos.caesarstone.com.

STORAGE:

Store properly in a closed and covered area. Avoid strong impacts that could break the material. Do not store near acids. If slabs contact some acids, damage/discoloration to the surface may occur.

SPECIFIC END USES:

No specific recommendations for end users.

² According to Standards for Gloves - EN 388: 2003.

8. Exposure Controls/Personal Protection

CONTROL PARAMETERS - OCCUPATIONAL EXPOSURE LIMITS (OEL):

There is no provision for any risk associated with the finished Caesarstone® Porcelain product. However, in cutting, grinding, polishing, drilling, etc. processes, dust containing crystalline silica (SiO₂), and other mineral dusts may be generated.

Employers should consult with a trained occupational safety and health professional in order to monitor the air in their workplace and in order to determine worker exposures to hazardous dust. Data collected during these evaluations should be compared with OELs applicable to each country.

OELs for respirable crystalline silica and cristobalite/tridymite, measured in mg/m³ for an 8-hour Time Weighted Average (TWA), are included in the following table. These limits may be changed from time to time and competent health and safety professionals or the local regulatory authority of the country in question should be consulted for the most up to date information.

EUROPEAN UNION	CRYSTALLINE SILICA (SiO ₂)	CRISTOBALITE & TRIDYMITE
Austria	0.05	0.15
Belgium	0.1	0.05
Czech Republic	0.1	0.1
Denmark	0.1	0.05
Finland	0.05	0.05
France	0.1	0.05
Germany ³	0.05	0.05
Greece	0.1	0.05
Ireland	0.1	0.05

³ Assessment criterium. Reference value. Germany no longer uses an OEL for quartz, cristobalite and tridymite. Employers are obliged to minimize exposure as much as possible, and to follow certain protective measures.

EUROPEAN UNION	CRYSTALLINE SILICA (SiO ₂)	CRISTOBALITE & TRIDYMITE
Israel	0.1	--
Italy	0.05	0.05
Netherlands	0.075	0.075
Norway	0.1	0.05
Poland	0.1	0.1
Portugal	0.025	0.025
Spain	0.05	0.05
Sweden	0.1	0.05
Switzerland	0.15	0.15
United Kingdom	0.1	0.1
European Directive ⁴	0.1	--

AUSTRALIA	CRYSTALLINE SILICA (SiO ₂)	CRISTOBALITE & TRIDYMITE
Australia	0.05	0.05 ⁵
New Zealand	0.05	0.05

⁴ European Directive 2004/37/EC was modified by European Directive 2017/2398 dated 27/12/2017 to include a limit value for occupational exposure to the respirable fraction of crystalline silica of 0.1 mg/m³.

⁵ Safe Work Australia recommended Dec 2019. Please refer to your respective State regulator.

US & CANADA	CRYSTALLINE SILICA (SiO ₂)	CRISTOBALITE & TRIDYMIT
USA, OSHA ^{6,7,8} PEL ⁷	0.05	0.05
ACGIH - TLV ^{7,9} (2019)	0.025	0.025
NIOSH - REL ⁷ (10-hour TWA)	0.05	0.05

SOUTH AFRICA	CRYSTALLINE SILICA (SiO ₂)	CRISTOBALITE & TRIDYMIT
South Africa	0.1	--

⁶ See OSHA - 29 CFR 1910.1053.

⁷ Abbreviations: see Section 16.

⁸ OSHA's 8-hour TWA Permissible Exposure Limit for particles not otherwise regulated is 5 mg/m³ for the respirable fraction and 15 mg/m³ for total dust.

⁹ The ACGIH's 8-hour TWA Threshold Limit Value for particles (insoluble or poorly soluble) not otherwise specific is 3 mg/m³ for respirable particles and 10 mg/m³ for inhalable particles.

Exposure Control

I MANUFACTURING & INSTALLATION:

Dust derived from the manufacturing processes could contain crystalline silica (SiO₂). Long-term exposure to crystalline silica (SiO₂) dust without the use of suitable protection may cause serious diseases as detailed in Section 2 and Section 11.

Employers should consult with a trained occupational safety and health professional in order to assess the employer's engineering controls and crystalline silica programs, policies and procedures and monitor the air in their workplace and in order to determine worker exposures to hazardous dust and comply with applicable local regulations.

Fabricate in a well-ventilated area and use local exhaust venting and other engineering controls to maintain the ambient workplace atmosphere below the relevant occupational exposure limits. Use respiratory protective equipment and other personal protective equipment. Restrict access to hazardous dust areas. Wash face and hands thoroughly after fabricating, installing or removing/demolishing the product. Do not eat, drink or smoke when fabricating this product. Leave working clothes at the workplace and wash separately.

Exposure to dust may be monitored and controlled with suitable control measures such as:

I ENGINEERING CONTROLS:

CNC machines, wet cutting methods, and local exhaust ventilation are recommended to reduce generation of dust. When Fabricating the product, installing or removing/demolishing the installed product, use equipment with integral dust collection and/or use local exhaust ventilation in a safe manner to maintain the ambient workplace atmosphere below the relevant occupational exposure limits.

I CLEANING AND MAINTENANCE:

Use HEPA vacuum and/or water cleaning systems. Never dry sweep or use compressed air, which cause dust to be airborne.

I PREVENTIVE MAINTENANCE PROGRAMMES:

Preventive maintenance programmes should be developed to ensure a correct procedure for the cleaning and operation of work equipment.

Personal Protective Equipment

RESPIRATORY PROTECTION:

Properly fitted respiratory protection equipment approved by the National Institute for Occupational Safety and Health (NIOSH; USA) for protection against dusts and organic vapours is necessary to avoid inhalation of crystalline silica during the Fabrication process of the product, and other processes that generate dust. The appropriate respirator selection depends on the type and magnitude of exposure.¹⁰ Use a positive pressure air supplied respirator if there is a potential for an uncontrolled release, exposure levels are not known, or under any other circumstance where air purifying respirators may not provide adequate protection.

EYE/FACE PROTECTION:

During Fabrication and installation, use dust proof goggles or safety glasses with side shields.¹¹ Have an emergency eyewash station available in areas where the product is Fabricated.

HAND AND SKIN PROTECTION:

Cotton or leather work gloves¹² and steel-toed shoes should be worn when handling and transporting the product. During Fabrication and installation processes protective clothing should be worn to minimize skin exposure to dusts and/or cuts. Wash hands before eating, drinking, smoking, or using toilet facilities. Wash thoroughly after work using soap and water. Promptly remove dusty clothing and launder safely, preferably on site, separately from other clothes, before reuse. Dusty clothing is a source of respirable silica and dusty clothing should be handled cautiously.

MEDICAL SURVEILLANCE:

Each worker should undergo relevant health surveillance prior to exposure and at regular intervals thereafter.

In no case are these safe and health measures and guides exhaustive or substitutive of the legal obligations in regards of health and safety under the applicable local regulations.

¹⁰ According to 29 CFR 1910.134 for appropriate NIOSH approved respirators, NIOSH Pocket Guide to Chemical Hazards, DHHS (NIOSH) Publication No. 2001-145 for equipment selection and EN-143: 2001 and its revisions EN-143/AC: 2002, and EN-143/AC: 2005.

¹¹ According to 29 CFR 1910.133 or European Standard EN166

¹² According to Standards for Gloves - EN 388: 2003

9. Physical and Chemical Properties

- **Physical state:** Solid Porcelain
- **Appearance:** Multi-coloured Porcelain
- **Odour:** Odourless
- **pH:** *N/A
- **Melting Point/Freezing Point:** *N/A
- **Initial Boiling Point/Boiling Range:** *N/A
- **Flash Point:** *N/A
- **Evaporation Rate:** *N/A
- **Flammability:** EN 13501- Not combustible
- **Upper and Lower Flammability/Explosive Limits:** *N/A
- **Fire-resistant:** A1, s0-d0 without reinforcing mesh (EN 13501); A2, s1-d0 with reinforcing mesh
- **Relative Density (EN ISO 10545-3):** 2300-2500 kg/m³
- **Kinematic Viscosity:** *N/A
- **Solubility:** Insoluble in water
- **Partition coefficient n-octanol/water:** *N/A
- **Linear Thermal Expansion (EN ISO 10545-8):** $\leq 6.5 \cdot 10^{-6} \text{ }^{\circ}\text{C}^{-1}$
- **Vapour Pressure:** *N/A
- **Vapour Density:** *N/A
- **Auto Ignition Temperature:** *N/A
- **Decomposition Temperature:** *N/A
- **Particle characteristics:** *N/A

*N/A: there is no applicable information related to the finished product.

10. Stability and Reactivity

REACTIVITY:

The product is stable under normal conditions of use, storage, and transport.

CHEMICAL STABILITY:

Stable at normal temperatures and storage conditions.

POSSIBILITY OF HAZARDOUS REACTIONS

None

CONDITIONS TO AVOID:

Avoid contact with surfaces whose temperature is over 250°C, as the material may deteriorate. Avoid strong impacts that may cause the material to break.

INCOMPATIBILITY WITH OTHER MATERIALS:

This product is incompatible with hydrofluoric acid.

HAZARDOUS DECOMPOSITION PRODUCTS:

If the product is reinforced on the back side with an embedded fiberglass mesh, the binder and adhesive components start degrading at temperatures over 200°C with formation of gases that may contain various hydrocarbons, carbon dioxide, carbon monoxide, nitrogen oxides, hydrogen cyanide and partially un-burnt carbon compounds, depending on the combustion conditions.

11. Toxicological Information

No acute or chronic effects are known from exposure to the intact product.

PRIMARY ROUTES OF EXPOSURE:

None for intact product. Inhalation and potential exposure to eyes, hands, or other body parts if contact is made with dust emitted from Fabrication Processes, and/or for operations involving the removal of the installed product.

ACUTE EFFECTS:

Breathing dust may cause acute mechanical respiratory irritation, including coughing, wheezing or difficulty breathing.

SKIN CORROSION/IRRITATION:

Skin contact may cause mechanical irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Eye contact may cause mechanical irritation.

RESPIRATORY EFFECTS:

- **Crystalline Silica (SiO₂)**
- **Silicosis** - Repeated, long-term exposure to respirable crystalline particles of a very small size (less than 10 microns) may cause silicosis, an incurable, progressively disabling and sometimes fatal lung disease. Silica dust particles become trapped in lung tissue, causing inflammation and scarring and reducing the lungs' ability to take in oxygen. Symptoms of silicosis can include progressive shortness of breath, cough and fatigue. Safety measures including wet processing and the use of effective respiratory protection will reduce the burden of inhaled dust and prevent the disease.
- **Acute silicosis** can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

CARCINOGENICITY:

The following components are listed by IARC, NTP, OSHA, ACGIH, WES NZ, HCIS or EU (Directive 2004/37/CE) as carcinogens.

Material	IARC	NTP	OSHA	ACGIH	WES NZ	HCIS	EU
Silica, Crystalline (quartz and cristobalite)	Group 1 carcinogenic to humans	known to be a carcinogen	Yes regulates as carcinogen	A2 Suspected Human Carcinogen	Confirmed Carcinogenic	Category 1A	Carcinogenic Category 1A

TERATOGENICITY:

No Data

MUTAGENICITY:

No Data

NAME OF TOXICOLOGICALLY SYNERGISTIC PRODUCTS:

No Data

SPECIFIC TARGET ORGAN TOXICITY SINGLE AND REPEATED EXPOSURE:

Silicosis is caused by the inhalation and retention of respirable crystalline silica dust. Silicosis can exist in several forms, chronic and accelerated (acute). Chronic silicosis is the most common form of silicosis and can occur after many years of exposure to relatively low levels of airborne respirable crystalline silica dust. It is further defined as either simple or complicated silicosis. Simple silicosis is characterized by lung lesions (shown as radiographic opacities) less than 1 centimetre in diameter, primarily in the upper lung zones. Simple silicosis may not be associated with symptoms, detectable changes in lung function, or disability. Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF). Complicated silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than 1 centimetre in diameter. Symptoms, if present, are shortness of breath, wheezing, cough, and sputum production.

TOXICITY TESTING DATA

Crystalline Silica:

Inhalation (human) LCLo: 0.3mg/m³/10Y

Inhalation (human) TCLo: 16mppcf/8H/17,9Y

Intermittent; focal fibrosis, (pneumoconiosis), cough, dyspnea

Inhalation (rat) TCLo: 50mg/m³/6H/71W

Intermittent; liver - tumors -

Oral LD50 RAT: 500 mg/kg

SENSITIZATION:

No Data

REPRODUCTIVE EFFECTS:

No Data

DEVELOPMENTAL EFFECTS:

No Data

12. Ecological Information

Ecotoxicity is expected to be low, based on insolubility (pieces of Caesarstone® Porcelain slabs, or silica dust) in water. Caesarstone® Porcelain does not contain ecotoxins and also due to its physical-chemical nature, it is not conducive to the growth of microorganisms on its surface.

ENVIRONMENTAL TOXICITY:

This product is not known to be toxic to the environment. No applicable data is available regarding persistence and degradability, bioaccumulative potential, mobility in soil, endocrine disrupting properties or other adverse effects.

RESULTS OF PBT AND vPvB ASSESSMENT:

This mixture does not meet bioaccumulative of toxic (PBT) or very persistent or very bioaccumulative (vPvB) standards according to Regulation (EC) No. 1907/2006, Annex XIII.

ISO 14001 CERTIFICATION:

Caesarstone® is ISO 14001 certified for Environmental Management Systems.

GREENGUARD CERTIFICATION:

Caesarstone® is compliant with GREENGUARD standard.

NSF CERTIFICATIONS:

Please refer to the NSF website at www.nsf.org regarding products certified by NSF.

13. Disposal Considerations

WASTE DISPOSAL METHOD:

Preferred options for disposal are (1) recycling, and (2) landfill. Performance of landfill should be made in an appropriate waste disposal facility approved by local authorities.

All disposal must be carried out in accordance with all the laws, requirements and guidelines applicable in the location of the user of Caesarstone® products.¹³ The product packaging material should be disposed in dedicated recycling bins, according to applicable local regulations.

14. Transportation Information

The product is not classified as dangerous according to land transport, air and sea regulations.

ADR¹⁴/UN Number/ RID¹⁴/IMO¹⁵/ ICAO¹⁶/US DOT¹⁷/ Packaging group	Proper Shipping Name	Not Regulated
	Hazard Class	Not Regulated
	ID Number	Not Regulated
	Packaging Group	Not Regulated
	Environmental hazards	No
	Special precautions for user	Not Regulated

¹³ 91/156/EEC and 199/31/CEE and the law 10/98, April 21 and RD 1481/2001, 27 December.

¹⁴ ADR and RID stand for the European Agreements Concerning the International Carriage of Dangerous Goods by Rail (RID) and by Road (ADR) and the Joint meeting of RID Safety Committee and the Working Party on the Transport of Dangerous Goods (WP.15). The RID Safety Committee and WP.15 administer the European Agreements governing the Regulations Concerning the International Transport of Dangerous Goods by Rail (RID) and Road (ADR), respectively.

¹⁵ International Classes for Dangerous Goods

¹⁶ International Civil Aviation Organization

¹⁷ Department of Transportation

15. Regulatory Information

This Safety Data Sheet (SDS) is according to (EC) No 1272/2008, (EC) No. 2020/878 and the CLP Regulation.

INTERNATIONAL LEGISLATION:

Globally Harmonized System of Classification and Labelling of Chemicals (GHS) (Latest 2017 edition) - UN

U.S. FEDERAL REGULATIONS:

SARA Title III¹⁸ Hazard Classes:

- Fire Hazard: No
- Reactive Hazard: No
- Release of Pressure: No
- Acute Health Hazard: No
- Chronic Health Hazard: Yes

OSHA COMMUNICATION STANDARD:

This product meets the definition of a health hazard under 29 CFR Section 1910.1200.

TSCA:¹⁹

All components of this product are on the TSCA inventory or are exempt from TSCA Inventory requirements.

U.S. STATE REGULATIONS:



California Prop 65 List: Crystalline silica is classified as a substance known to the State of California to be a carcinogen.

INVENTORY INFORMATION:

The substances in this preparation have been checked against the EINECS²⁰, ELINCS²¹, and the NLP²² list. Substances not identified on these inventories are exempt from notification requirements. (The EINECS number for Quartz: 238-878-4).

¹⁸ Superfund Amendments and Reauthorization Act - Title III of SARA is the Emergency Planning and Community Right-To-Know Act (EPCRA).

¹⁹ Section 8 (b) of the Toxic Substances Control Act (TSCA) requires EPA to compile, keep current and publish a list of each chemical substance that is manufactured or processed, including imports, in the United States for uses under TSCA inventory.

²⁰ European Inventory of Existing Commercial Chemical Substances

²¹ European List of Notified Chemical Substances

²² No Longer Polymer

■ EUROPEAN REGULATIONS:

- Regulation (EC) 1907/2006 (REACH) OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006, concerning the Registration, Evaluation, Authorization and Restriction of Chemicals, updated according to Regulation (EU) 2015/830 of 28 May 2015, which modifies Regulation EC) No. 1906/2006.
- European Directive 2004/37/EC, modified by European Directive 2017/2398 dated 27/12/2017.
- Regulation (EC) No. 1907/2006 REACH, Annex XIV List of substances subject to authorization, with its later modifications: Not present, or not present in regulated quantities.
- Regulation (EC) No. 1272/2008 (CLP) OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures.
- REGULATION (EU) 2016/918 OF THE COMMISSION of 19 May 2016 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No. 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures.

■ AUSTRALIA AND NEW ZEALAND REGULATIONS:

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals:
<http://hcis.safeworkaustralia.gov.au/>
- New Zealand Workplace Exposure Standards (WES): <https://worksafe.govt.nz>
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

16. Other Information

The product should be used according to manufacturer using instructions and local regulations Hazard Ratings according to: NFPA(R)²³ and HMIS.²⁴

- Health Hazard: 1
- Flammability: 0
- Reactivity: 0

Key Legend Information:

ACGIH	American Conference of Governmental Industrial Hygienists
IARC	International Agency for Research on Cancer
OSHA	Occupational Safety and Health Administration
NA	Not Applicable
NTP	National Toxicology Program
REL	Recommended Exposure Limits
PEL (OSHA)	Permissible Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average
NIOSH	National Institute for Occupational Safety and Health
HCIS	Hazardous Chemical Information System - Safe Work Australia
WES NZ	Workplace Exposure Standards New Zealand

²³ National Fire Protection Association

²⁴ Hazardous Materials Identification System

References

- Registry for Toxic Effects of Chemical Substances (RTECS), 2006.
- OSHA/NIOSH Worker Exposure to Silica during Countertop Manufacturing, Finishing and Installation, 2015
<http://www.cdc.gov/niosh/docs/2015-106/pdfs/2015-106.pdf>
- Centers for Disease Control and Prevention (CDC) Morbidity and Mortality Weekly Reports, Silicosis mortality trends and new exposures to respirable crystalline silica - U.S., 2001-2010. (February 13, 2015).
- NIOSH Hazard Review – Health Effects of Occupational Exposure to Respirable Crystalline Silica, April 2002.
- NTP Eleventh Report on Carcinogens, 2005.
- IARC Monograph Volume 68, Silica, Some Silicates and Organic Fibres, 1997.
- IARC Monograph; 14th Report on Carcinogens. 2016. Silica, Crystalline (Respirable Size)
<https://ntp.niehs.nih.gov/pubhealth/roc/index-1.html#toc1>
- Hazardous Substances Data Bank (HSDB), 2004, 2006.
- Documentation of the TLV – Silica, Crystalline: α -Quartz and Cristobalite, American Conference of Governmental Industrial Hygienists, 2006.

The information contained herein is believed to be correct and represents the best information currently available for Caesarstone®. However, Caesarstone makes no warranties, expressed or implied, of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from the use thereof. Under no circumstances does the data contained in this Safety Data Sheet constitute a guarantee of specific properties other than such properties explicitly mentioned in this SDS or create any contractual relationship. The user of the product only is responsible for determining the suitability of Caesarstone's products for its particular application.

It is the exclusive responsibility of the recipient of our product to find out the applicable laws, rules, practices and regulations prior to using the product and to comply with them in all respects. You should note that applicable national and international regulations and laws may change from time to time and it is your responsibility to follow such changes.

The contents of this Safety Data Sheet must not be interpreted as a recommendation to use any product in violation of the laws or safety practices.

Further information is available at <https://www.osha.gov/silica> and at <http://www.nepsi.eu> and in the Guide to Good Practice for the Agreement on Workers' Health Protection Through the Good Handling and Use of Crystalline Silica and Products Containing It, published by NEPSI. See also the Caesarstone website for safety instructions and recommendations at: mos.caesarstone.com.

